

IDF350 Series



Standard Features

- -Fully Insulated Jacket
- -Industrial Grade Burner
- -Stainless Steel Heat Exchanger
- -Satin Coated Steel w/ Powder Coated Paint -EZ Ball-Valve Switch Over (LP/NG)
- -Independent Fan & Blower
- -Heavy Duty 6-Ply Pneumatic Tires
- -Polarity & Running Lights
- -Flexible Duct Attachment Pin Lock or **Belt Cuff**

- -GenySis Primary Control w/ Diagnostic Reader (Oil)
- -42 US Gallon DW Fuel Tank w/ Gauge (Oil)
- -3 Trials For Ignition (LP/NG)
- -Automatic High Limit Safety Switch-off
- -Lifting Bail
- -CSA Certified

Specifications	IDF350 LP/NG (blu	ue) IDF350-II (red)
----------------	-------------------	---------------------

- BTU/h - Fuel Type -CFM -Fan Motor -Static Pressure -Flue Size -Outlet Configuration -Electrical Requirements
- -Net Weight -Dimensions (LxWxH) -Crated Shipping Dimensions -Crated Shipping Weight
- 350,000 Propane/Natural Gas 2,500 ½HP 1,800RPM .5"
- 6" Dual 12" or Single 16" 110-120V/15amp
- 420lbs 70" x 35" x 52" 83" x 37" x 52" 580lbs

- 350,000 Oil/Diesel/Kerosene 2,500
- ½HP 1,800RPM
- .5" 6"
- Dual 12" or Single 16" 110-120V/15amp
- 420lbs
- 70" x 35" x 52" 83" x 37" x 52" 580lbs